

EGU21-13138

<https://doi.org/10.5194/egusphere-egu21-13138>

EGU General Assembly 2021

© Author(s) 2021. This work is distributed under the Creative Commons Attribution 4.0 License.



Challenges and opportunities from large volume, multi-offset Ground Penetrating Radar data

Dimitrios Angelis¹, Craig Warren¹, Nectaria Diamanti², James Martin¹, and Peter Annan³

¹Mechanical and Construction Engineering, Northumbria University, Newcastle Upon Tyne, United Kingdom

²Department of Geophysics, School of Geology, Aristotle University of Thessaloniki, Greece

³Sensors & Software Inc. Mississauga, Canada

The most frequently used survey mode for acquiring Ground Penetrating Radar (GPR) data is common offset (CO) – where a single transmitter and receiver pair move along a survey line at a constant (offset) separation distance. This allows rapid and dense data acquisition, and therefore high-resolution large-scale investigations, to be carried out with relative ease, and at relatively low cost. However, it has long been known that multi-offset survey methods, such as common mid-point (CMP) and wide-angle reflection-refraction (WARR), can offer many benefits over CO: detailed subsurface EM wave velocity models; enhanced reflection sections with higher signal-to-noise ratio (SNR); the potential to adapt well-established advanced seismic processing schemes for GPR data [1-2].

Despite the advantages of multi-offset GPR data, these methods have seen limited adoption as, in the past, they required significantly more time, effort, and hence cost, to collect. However, recent advances in GPR hardware, particularly in timing and control technology, have enabled the development of multi-concurrent sampling receiver GPR systems such as the “WARR Machine” manufactured by Sensors & Software Inc. [3-4]. These newly developed GPR systems have the potential to provide all the aforementioned benefits with considerably less effort and therefore reduced survey cost, as they allow for the fast acquisition of multi-offset WARR soundings.

In this work, we look at the challenges and opportunities from collecting and processing multi-offset GPR data. We demonstrate a processing workflow that combines standard GPR processing approaches, with methods adapted from seismic processing, as well as our own algorithms. This processing framework has been implemented into a GUI-based software written in MATLAB [5], and has been tested using both synthetic [6] and real multi-offset GPR data. Some of the specific challenges with multi-offset GPR that we investigate are time zero misalignments, CMP balancing, velocity analysis, and automated velocity picking. We show how addressing these issues can result in improved velocity analysis, and ultimately in improved subsurface velocity models, and stacked sections.

References

[1] Ursin, B., 1983. Review of elastic and electromagnetic wave propagation in horizontally layered

media. *Geophysics*, 48(8), pp.1063-1081.

[2] Carcione, J. and Cavallini, F., 1995. On the acoustic-electromagnetic analogy. *Wave Motion*, 21(2), 149-162.

[3] Annan, A. P., and Jackson, S., 2017. The WARR machine. 2017 9th International Workshop on Advanced Ground Penetrating Radar (IWAGPR).

[4] Diamanti, N., Elliott, J., Jackson, R. and Annan, A. P., 2018, The WARR Machine: System Design, Implementation and Data: *Journal of Environmental & Engineering Geophysics*, 23, pp.469-487.

[5] Angelis, D., Warren, C. and Diamanti, N., 2020. A software toolset for processing and visualization of single and multi-offset GPR data. 18th International Conference on Ground Penetrating Radar.

[6] Warren, C., Giannopoulos, A. and Giannakis, I., 2016. gprMax: Open source software to simulate electromagnetic wave propagation for Ground Penetrating Radar. *Computer Physics Communications*, 209, pp.163-170.